



**DE-150P**

1+1  
Tela+Plástico  
Cloth+Plastic  
Toile+Plastic



**DC-350**

Aspirador ciclónico.  
Separador de polvo-serrín-  
viruta. Filtro cartucho con  
limpieza manual  
*Cyclone dust collector.  
Dust and chip separation.  
Cartridge filter with manual  
cleaner*  
*Aspíteur cyclonique.  
Separation de poussière et  
copeaux. Filtre de cartouche  
avec nettoyage manuel*



**AP-1200/50L**



**ACCESORIOS ASPIRADORES  
DUST COLLECTOR ACESORIES  
ACCESSOIRES D'ASPIRATEUR**



	AP-1200/50	DE-150P	DC-350
Potencia motor Motor power Puissance moteur	1,5 Hp. (Mono.220V)	1 Hp. (Mono.220V)	3 Hp. (Tri.380V)
Caudal aspirable Air speed Débit d'aspiration	190 m <sup>3</sup> /h	1.100 m <sup>3</sup> /h	1.200 m <sup>3</sup> /h
Capacidad deposito Deposit capacity Capacité cuve	50 L	-	-
Ø Ventilador Fan Ø Ø Ventilateur	-	230 mm. (metal)	356 mm. (metal)
Ø Sacos Bags Ø Ø Sacs	-	370 x700 mm.	470x920 mm + 370x750 mm
Ø Filtros Filter Ø Ø Filtres	-	370 x700 mm.	340 x 800 mm.
Filtros Filter Filtres	0.5 Micron	5 Micron	1 Micron
Ø Toma aspiración Dust inlet Ø Ø Buse d'aspiration	5 x 100/68/45/40/35 mm.	100 mm.	2 x 100 mm.
Ø Boca de aspiración Main dust inlet Ø Ø Bouche d'aspiration	100 mm.	100 mm.	125 mm.
Nivel sonoro Noise level Niveau sonore	-	85 db.	80 db.
	360 x 730 mm.	950x450x1500 mm.	1132 x 750 x 1930 mm.
	10 Kg.	35 Kg.	78 Kg.