



DC-350

Aspirador ciclónico
 Separador de polvo-serrín-viruta
 Filtro cartucho con limpieza manual
Cyclone dust collector
Dust and chip separation
Cartridge filter with manual cleaner
 Aspateur cyclonique
 Separation de poussière et copeaux
 Filtre de cartouche avec nettoyage manuel



DE-150P

1+1
 Tela+Plástico
 Cloth+Plastic
 Toile+Plastic



AP-1200/50L

	AP-1200/50	DE-150P	DC-350
Potencia motor Motor power Puissance moteur	1,5 Hp. (Mono.220V)	1 Hp. (Mono.220V)	3 Hp. (Tri.380V)
Caudal aspirable Air speed Débit d'aspiration	190 m ³ /h	1.100 m ³ /h	1.200 m ³ /h
Capacidad deposito Deposit capacity Capacité cuve	50 L	-	-
Ø Ventilador Fan Ø Ventilateur	-	230 mm. (metal)	356 mm. (metal)
Ø Sacos Bags Ø Sacs	-	370 x700 mm.	470x920 mm + 370x750 mm
Ø Filtros Filter Ø Filtres	-	370 x700 mm.	340 x 800 mm.
Filtros Filter Filtres	0.5 Micron	5 Micron	1 Micron
Ø Toma de aspiración Dust collector Ø Buse d'aspiration	5 x 100/68/45/40/35 mm.	100 mm.	2 x 100 mm.
Ø Boca de aspiración Main dust inlet Ø Bouche d'aspiration	100 mm.	100 mm.	125 mm.
Nivel sonoro Noise level Niveau sonore	-	85 db.	80 db.
	360 x 730 mm.	950 x 450 x 1500 mm.	1132 x 750 x 1930 mm.
	10 Kg.	35 Kg.	78 Kg.