



LIJADORA DE DOS RODILLOS

TWO ROLLERS SANDER

PONÇEUSE DE DEUX ROULEAUX

## LR-600/2N

### LR-600/2N

Potencia motor	<i>Motor power</i>	<i>Puissance moteur</i>	3 Hp. (Mono.220V)
Ancho de Lijado	<i>Sander belt size</i>	<i>Dimensions bande</i>	635 mm.
Grueso Mín./máx.	<i>R.p.m.</i>	<i>R.p.m</i>	6 / 125 mm.
Velocidad avance	<i>Table tilt</i>	<i>Inclinaison table</i>	2 - 9 m/min.
R.p.m.	<i>Sander group tilt</i>	<i>Inclin. groupe ponçage</i>	1.600
Potencia motor avance	<i>Table dimensions</i>	<i>Dimensions table</i>	1/8 Hp.
Ø Rodillo lijador	<i>Auxiliary table dimen.</i>	<i>Dimen. table auxiliaire</i>	127 mm.
Ø Toma de aspiración	<i>Oscilating travel</i>	<i>Course oscilation</i>	2 x 105 mm.
Medidas máquina	<i>Machine dimensions</i>	<i>Dimensions de la machine</i>	1.270 x 790 x 1.270 mm.
Peso máquina	<i>Machine Weight</i>	<i>Poids de la machine</i>	220 Kg.
Medidas embalaje	<i>Packaging Dimensions</i>	<i>Dimensions de l'emballage</i>	1.200 X 830 X 1.310 mm.
Peso embalaje	<i>Packaging Weight</i>	<i>Poids de l'emballage</i>	260 Kg.